


MISCELLANEOUS

GUN LOCKS


- The world standard in trigger lock design.
- Steel and zinc body for maximum durability.
- 4-pin tumbler cylinder helps prevent picking.
- Durable metal construction
- Protective rubber parts shield gun from scatching or marring.
- Fits many handguns, rifles and shotguns.



Master Lock



- Easy to install and set.
- Features positive locking with adjustable ratchet mechanism.
- Offers added convenience of a keyless resettable combination.
- Protective rubber parts shield gun from scatching or marring.
- Fits many handguns, rifles and shotguns.




Keyed Different

90D

Keyed Alike*

90D KA



Resettable Combination


94DSPT

*KEYED ALIKE NUMBERS STOCKED:

90KA: P104.

HAND RAIL BRACKETS


CAL-ROYAL



CR-HDHB40


US-3, 5, 10B, 15, 15A, 26, 26D
Heavy Duty Hand Rail Bracket
(2-1/4" H x 1-3/8"W)
(Ives #059)

DON-JO



DJ-130

Finishes: 605, 609, 613, 619, 620, 625, 626
Material: Cast Aluminum. Base: 2-13/16" x 1-1/2". ANSI L33061.



DJ-135

Finishes: 605, 613, 619, 620, 626
Material: Solid Brass. Base: 2-1/4" x 1-1/4". ANSI L13061.

Hand Rail Bracket

- 059 made from solid brass, cast aluminum or epoxy-coated aluminum.
- 59 made from cast brass or cast aluminum.
- Large faceplate for secure attachment to wall.
- Features solid construction for increased strength.
- 59 conforms to ANSI/BHMA A156.16 L13061 for brass and L33061 for aluminum.
- Dimensions:


IV-059A & IV-059B:

Base: 2-1/4" H x 1-3/8" W
Base to Center of Rail: 2-7/16"

IV-59A: Base: 2-13/16" H x 1-1/2" W
Base to Center of Rail: 2-3/4"

IV-59B: Base: 2-15/16" H x 1-1/2" W
Base to Center of Rail: 2-3/4"

IVES



Stock No. (Specify Finish)

IV-059A Cast Aluminum

Finishes: 3, 5, 10B, 14, 92

IV-059B Solid Brass

Finishes: 3, 10B, 15, 15A, 26

Stock No. (Specify Finish)

IV-59A Cast Aluminum

Finishes: 3, 5, 10B, 14, 92

IV-59MB Cast Brass


Finishes: 3, 5, 10B, 15, 15A, 26, 26D

MISCELLANEOUS

HAND RAIL BRACKETS

Hand Rail Bracket


- For use on commercial applications.
- Exceeds OSHA and BHMA strength test requirements.
- Cast aluminum construction.
- Packed with toggle bolt and screws.
- Meets ANSI/BHMA A156.16, L33101.
- Dimensions:
3-1/8" Base Diameter
3-1/8" Base to Rail Center



Stock No. (Specify Finish)
IV-HB158
Finishes: 3AL, 27

Hand Rail Bracket


- For use on commercial applications.
- Exceeds OSHA and BHMA strength test requirements.
- Packed with square head iron lag screw, expansion shield and screws.
- Cast Aluminum construction for the HB159A.
- HB159A meets ANSI/BHMA A156.16, L33081.
- Dimensions:
3-1/8" Base Diameter, 3-1/8" Base to Rail Center



Stock No. (Specify Finish)
IV-HB159
Finishes: 3AL, 27


Adjustable Hand Rail Bracket

- For horizontal rail installations in institutional and commercial buildings.
- Rust resistant.
- Exceeds OSHA and BHMA strength test requirements.
- Adjustable brackets compensate for irregularities in wall, adjustable from 1-1/2" to 2" wall clearance.
- Stainless steel 1/4"-20 button head socket screw and stainless steel self-locking hex nut provide strong, rigid assembly.
- Extruded aluminum construction.
- Screws with expansion shields.
- Dimensions:
2-3/4" Tall x 1-3/4" Wide



Stock No. (Specify Finish)
IV-HB162 28
Finishes: 28


HOOKS — COAT, HAT, ETC.



DON-JO

DJ-300
Finishes: 605, 613, 619, 620, 625, 626
Material: Cast Brass.

DJ-302
Finishes: 605, 613, 619, 620, 625, 626
Material: Cast Brass.



Stock No. (Specify Finish)
IV-571A
Finishes: 3, 92

Coat & Hat Hook

- All-purpose hook in traditional design.
- Made from cast aluminum.
- Conforms to ANSI/BHMA A156.16 L33113 for aluminum.
- Dimensions:
Base: 1-3/4" H x 1-1/4" W
Projection: 3"

©ZIPF LOCK COMPANY

See page 427 for Cal Royal, Don Jo, Ives finish descriptions.

441
(PL-42)